



SDR-2100



Model	SDR-2100
Frequency Range	UHF 600 - 900MHz
Switching Bandwidth	25MHz
Switchable Frequencies	100
Channels	2
Display Screen	7-segment LED
Oscillation Type	PLL Synthesized
Frequency Stability	$\pm 0.005\%$
Receiving Method	Diversity
Sensitivity	-100dBm at S/N ratio >80dB
Image Rejection	> 85dB
S/N Ratio	> 110dB
Peak Deviation	$\pm 40\text{KHz}$
T.H.D	< 0.5%
Antenna Socket	TNC type
Audio Outputs	Unbalanced: +4dBm(1.25V) / 5K Ω Balanced: -18dBm(50mV) / 600 Ω
Squelch	Noise squelch & Pilotone squelch
Power Supply	100-240V AC, 12V DC/2.0A
Rack Size	Standard 1-rack (metal)
Dimension (L x W x H)	42.5 x 22 x 5 cm / 16.5 x 9 x 2 inch (Body only) 42.5 x 22 x 23 cm / 16.5 x 9 x 9 inch (with vertical Antenna)



Winfull International Technology Ltd

Unit H, 2/F., Hop Hing Ind. Bldg., 704 Castle Peak Road, Kowloon

Tel.: 27456880 Fax: 2307 0648 Website: www.winfull.com.hk

E-mail: info@winfull.com.hk